

Mei£! gate paper 2009

Food & Diet



**ASSIGN
BUSTER**

MEIÉ! GATE Paper 2009 www. gateforum. com _____ Download from
 wQ. No. 1 — 20 Carry One Powered By © JbigDeaL _____ ww. JbigDeaL.
 com Mark Each 1. iÉ®3 iÉˆ5 For a matrix $[M] = \begin{bmatrix} iÉ & iÉ^x & iÉ^y \\ iÉ^z & iÉ^t & iÉ^u \end{bmatrix}$,
 the transpose of the matrix is equal to the inverse of $3iÉ^z \ 5iÉ^t \ iÉ^u$ the
 matrix $iÉ^z \ iÉ^t \ iÉ^u = iÉ^z \ iÉ^t \ iÉ^u$. The value of x is given by $iÉ^z \ iÉ^t \ iÉ^u$ (A) $iÉ^z \ iÉ^t \ iÉ^u$
 4 5 3 5 (D) 4 5 (B) $iÉ^z \ iÉ^t \ iÉ^u$ (C) $3(s^2 + 1 + s)$ (D) 0 (C) $iÉ^z \ iÉ^t \ iÉ^u$ (D) $1 + e^{iÉ^z \ iÉ^t \ iÉ^u}$
 is If three coins are tossed simultaneously, the probability of getting at least
 one head (A) $1/8$ 5. (C) (B) 4 The inverse Laplace transform of (A) $1 + e^{iÉ^z \ iÉ^t \ iÉ^u}$ 4. 3
 5 $iÉ^z \ iÉ^t \ iÉ^u$ The divergence of the vector field $3xz\hat{i} + 2xyj + yz^2k$ at a point (1,
 1, 1) is equal to i (A) 7 3. (B) $iÉ^z \ iÉ^t \ iÉ^u$ (B) $3/8$ (C) $1/2$ (D) $7/8$ If a closed system is
 undergoing an irreversible process, the entropy of the system (A) Must
 increase (B) Always remains constant (C) Must decrease (D) Can increase,
 decrease or remain constant 6. A coolant fluid at 30°C flows over a heated
 flat plate maintained at a constant temperature of 100°C . The boundary
 layer temperature distribution at a given location on the plate may be
 approximated as $T = 30 + 70 \exp(-y)$ where y (in m) is the distance
 normal to the plate and T is in $^\circ\text{C}$. If thermal conductivity of the fluid is 1.0 W/mK , the local convective heat transfer coefficient (in $\text{W/m}^2\text{K}$) at that
 location will be (A) 0. 2 7. (B) 1 (C) 5 (D) 10 A frictionless piston-cylinder
 device contains a gas initially at 0.8 MPa and 0.015 m^3 . It expands quasi-
 statically at constant temperature to a final volume of 0.030 m^3 . The work
 output (in kJ) during this process will be (A) 8. 32 (B) 12. 00 (C) 554. 67 (D)
 8320. 00 1 © All rights reserved by GATE Forum Educational Services Pvt.
 Ltd. No part of this booklet may be reproduced or utilized in any form without
 the P age 1 of 13 written permission. Discuss this questions paper at www.
 gateforum. com. MEIÉ! GATE Paper 2009 www. gateforum. com 8. In an ideal
<https://assignbuster.com/me-gate-paper-2009/>

vapour compression refrigeration cycle, the specific enthalpy of

_____ Download from www. JbigDeaL. com Powered By ©

JbigDeaL_____ refrigerant (in kJ/kg) at the following states is given as:

Inlet of condenser: 283 Exit of condenser: 116 Exit of evaporator: 232 The

COP of this cycle is (A) 2. 27 9. (B) 2. 75 (C) 3. 27 (D) 3. 75 A compressor

undergoes a reversible, steady flow process. The gas at inlet and outlet of

the compressor is designated as state 1 and state 2 respectively. Potential

and kinetic energy changes are to be ignored. The following notations are

used: v = specific volume and P = pressure of the gas. The specific work

required to be supplied to the compressor for this gas compression process

is 2 (A) $\int_{v_1}^{v_2} P dv$ (B) $\int_{P_1}^{P_2} v dP$ (C) $v_1 (P_2 - P_1)$ (D) $\int_{v_1}^{v_2} P_2 dv$

A block weighing 981N is resting on a horizontal surface. The coefficient of

friction between the block and the horizontal surface is $\mu = 0.2$ A vertical

cable attached to the block provides partial support as shown. A man can

pull horizontally with a force of 100N. What will be the tension, T (in N) in the

cable if the man is just able to move the block to the right? T (A) 176. 2 (B) 11. 2 (C) 481. 0 (D) 981. 0

If the principal stresses in a plane

stress problem, are $\sigma_1 = 100\text{MPa}$, $\sigma_2 = 40\text{MPa}$, the magnitude of the

maximum shear stress (in MPa) will be (A) 60 (B) 196. 0 (C) 50 (D) 30

20 A simple quick return mechanism is shown in the figure. The forward to

return ratio of the quick return mechanism is 2: 1. If the radius of the crank

O_1P is 125 mm, then the distance 'd' (in mm) between the crank centre to

lever pivot centre point should be 2 © All rights reserved by GATE Forum

Educational Services Pvt. Ltd. No part of this booklet may be reproduced or

utilized in any form without the written permission. Discuss this

questions paper at www.gateforum.com. MEI gate Paper 2009 www.https://assignbuster.com/me-gate-paper-2009/

gateforum. com Q _____ Download from www. JbigDeaL. com Powered
By © JbigDeaL _____ O 1 P d O2 (A) 144. 3 13. (B) 216. 5 (D) 250. 0

The rotor shaft of a large electric motor supported between short bearings at both ends has a maximum deflection of 1.8 mm in the middle of the rotor. Assuming the rotor to be perfectly balanced and supported at knife edges at both the ends, the likely critical speed (in rpm) of the shaft is (A) 350 14. (C) 240. 0 (B) 705 (C) 2810 (D) 4430

A solid circular shaft of diameter d is subjected to a combined bending moment M and torque, T . The material property to be used for designing the shaft using the relation $M^2 + T^2 = k d^3$ is (A) ultimate tensile strength (S_u) (C) torsional yield strength (S_{sy}) 15. (B) tensile yield strength (S_y) (D) endurance strength (S_e) The effective number of lattice points in the unit cell of simple cubic, body centered cubic, and face centered cubic space lattices, respectively, are (A) 1, 2, 2 16. (B) 1, 2, 4 (C) 2, 3, 4 (D) 2, 4, 4

Friction at the tool-chip interface can be reduced by (A) decreasing the rake angle (C) decreasing the cutting speed 17. (B) increasing the depth of cut (D) increasing the cutting speed

Two streams of liquid metal, which are not hot enough to fuse properly, result into a casting defect known as (A) cold shut 18. (B) swell (C) sand wash (D) scab

The expected time (t_e) of a PERT activity in terms of optimistic time (t_0), pessimistic time (t_p) and most likely time (t_l) is given by (A) $t_e = \frac{t_0 + 4t_l + t_p}{6}$ (C) $t_e = \frac{t_0 + 4t_l + t_p}{3}$ (B) $t_e = \frac{t_0 + 4t_p + t_l}{6}$ (D) $t_e = \frac{t_0 + 4t_l + t_l}{3}$

© All rights reserved by GATE

Forum Educational Services Pvt. Ltd. No part of this booklet may be reproduced or utilized in any form without the P age 3 of 13 written

permission. Discuss this questions paper at www.gateforum.com. MEİİ

GATE Paper 2009 www.gateforum.com 19. Which of from www.gateforum.com is the

correct data Powered By © JbigDeaL _____ _____ Download the

<https://assignbuster.com/me-gate-paper-2009/>

following . JbigDeaL. com structure for solid models? (A) solid part faces edges vertices (B) solid part edges faces vertices (C) vertices faces solid parts (D) vertices

20. edges faces edges solid parts Which of the following forecasting methods takes a fraction of forecast error into account for the next period forecast? (A) simple average method (B) moving average method (C) weighted moving average method (D) exponential smoothing method

Q. No. 21 — 56 Carry Two Marks Each

21. An analytic function of a complex variable $z = x + iy$ is expressed as $f(z) = u(x, y) + iv(x, y)$ where $i = \sqrt{-1}$. If $u = xy$, the expression for v should be $(x + y)^2$ (A) $2x^2 + 2y^2 + k$ (B) $2x^2 - 2y^2 + k$ (C) $2x^2 + 2y^2 + k$ (D) $2x^2 - 2y^2 + k$

22. The solution of $x^2 + y^2 = 23$ is (A) $y = x^4 + 1$ (B) $y = x^2 + 1$ (C) $y = x^4 + 1$ (D) $y = x^5 + 1$

23. A path AB in the form of one quarter of a circle of unit radius is shown in the figure. Integration of $(x + y)$ on path AB traversed in a counter-clockwise sense (A) $\frac{1}{2}$ (B) $\frac{1}{\sqrt{2}}$ (C) $\frac{1}{2} + \frac{1}{\sqrt{2}}$ (D) $1 + \frac{1}{\sqrt{2}}$

24. The distance between the origin and the point nearest to it on the surface $z^2 = 1 + xy$ is (A) $\frac{1}{2}$ (B) $\frac{1}{\sqrt{2}}$ (C) $\frac{1}{2} + \frac{1}{\sqrt{2}}$ (D) $1 + \frac{1}{\sqrt{2}}$

25. The differential equation $dy + y = x^4$ with the condition $y(1) = 5$ has a solution (A) $(x^2 + y)^2 = x^2 + k$ (B) $3x^2 + k$ (C) $3x^2 + k$ (D) $2x^2 + k$

26. The area enclosed between the curves $y^2 = 4x$ and $x^2 = 4y$ is (A) $\frac{16}{3}$ (B) $\frac{8}{3}$ (C) $\frac{32}{3}$ (D) $\frac{16}{4}$

© All rights reserved by GATE Forum Educational Services Pvt. Ltd. No part of this booklet may be reproduced or utilized in any form without the written permission. Discuss this questions paper at www.gateforum.com. ME Gate Paper 2009 www.gateforum.com

27. The standard deviation of a uniformly distributed random variable between 0 and _____ is (A) $\frac{1}{\sqrt{12}}$ (B) $\frac{1}{\sqrt{3}}$ (C) $\frac{5}{\sqrt{12}}$ (D) $\frac{7}{\sqrt{12}}$

Consider steady, incompressible and irrotational flow through a reducer in a horizontal pipe where the diameter is reduced from 20cm to 10cm. The pressure in the

<https://assignbuster.com/me-gate-paper-2009/>

20cm pipe just upstream of the reducer is 150kPa. The fluid has a vapour pressure of 50kPa and a specific weight of 5 kN/m³. Neglecting frictional effects, the maximum discharge (in m³/s) that can pass through the reducer without causing cavitation is (A) 0.0528. (B) 0.16 (C) 0.27 (D) 0.38

In a parallel flow heat exchanger operating under steady state, the heat capacity rates (product of specific heat at constant pressure and mass flow rate) of the hot and cold fluid are equal. The hot fluid, flowing at 1kg/s with $C_p = 4\text{kJ/kgK}$, enters the heat exchanger at 102°C while the cold fluid has an inlet temperature of 15°C. The overall heat transfer coefficient for the heat exchanger is estimated to be 1kW/m²K and the corresponding heat transfer surface area is 5m². Neglect heat transfer between the heat exchanger and the ambient. The heat exchanger is characterized by the following relation: $2\hat{\mu} = 1 - \exp(-\hat{\mu}^2 NTU)$. The exit temperature (in °C) for the cold fluid is (A) 45.29. (D) 75 (B) 310 (C) 515 (D) 1032

An irreversible heat engine extracts heat from a high temperature source at a rate of 100kW and rejects heat to a sink at a rate of 50kW. The entire work output of the heat engine is used to drive a reversible heat pump operating between a set of independent isothermal heat reservoirs at 17°C and 75°C. The rate (in kW) at which the heat pump delivers heat to its high temperature sink is (A) 50.31. (C) 65

In an air-standard Otto cycle, the compression ratio is 10. The condition at the beginning of the compression process is 100kPa and 27°C. Heat added at constant volume is 1500kJ/kg, while 700kJ/kg of heat is rejected during the other constant volume process in the cycle. Specific gas constant for air = 0.287 kJ/kgK. The mean effective pressure (in kPa) of the cycle is (A) 103.30. (B) 55 (B) 250 (C) 300 (D) 360

You are asked to evaluate assorted fluid flows for their suitability in a given laboratory application. The

following three flow choices, expressed in terms of the two-dimensional velocity fields in the xy-plane, are made available. P. $u = 2y, v = \hat{a}^{\wedge}3x$ Q. $u = 3xy, v = 0$ R. $u = \hat{a}^{\wedge}2x, v = 2y$ 5 © All rights reserved by GATE Forum Educational Services Pvt. Ltd. No part of this booklet may be reproduced or utilized in any form without the P age 5 of 13 written permission. Discuss this questions paper at www.gateforum.com. MEİİ GATE Paper 2009 www.gateforum.com Which flow(s) should be recommended when the application JbigDeaL_____ Download from www.JbigDeaL.com Powered By ©requires the flow to be incompressible and irrotational? (A) P and R 32. (C) Q and R (D) R Water at 25°C is flowing through a 1. 0km long G. I pipe of 200mm diameter at the rate of 0. 07m³/s. If value of Darcy friction factor for this pipe is 0. 02 and density of water is 1000kg/m³, the pumping power (in kW) required to maintain the flow is (A) 1. 8 33. (B) Q (B) 17. 4 (C) 20. 5 (D) 41. 0 Consider steady-state heat conduction across the thickness in a plane composite wall (as shown in the figure) exposed to convection conditions on both sides. 1 2 $h_i, T_{\hat{a}}^{\wedge}z, i, h_0, T_{\hat{a}}^{\wedge}z, 0$ L1 L2 Given: $h_i = 20W / m^2K; h_0 = 50W / m^2K; T_{\hat{a}}^{\wedge}z, i = 200 C; T_{\hat{a}}^{\wedge}z, 0 = \hat{a}^{\wedge}20 C; k_1 = 20W / mK; k_2 = 50W / mK; L_1 = 0. 30m$ and $L_2 = 0. 15m$. Assuming negligible contact resistance between the wall surfaces, the interface temperature, T (in °C), of the two walls will be (A) -0. 50 34. (B) 2. 75 (C) 3. 75 (D) 4. 50 The velocity profile of a fully developed laminar flow in a straight circular pipe, as $R^2 \ll dp \ll r^2$ shown in the figure, is given by the expression $u(r) = \hat{a}^{\wedge} \ll dx \ll r^2$ where $4\mu \ll R \ll dp$ is a constant. The average velocity of fluid in the pipe is $\int_0^R u(r) r \times$ (A) $\hat{a}^{\wedge} R^2 \ll dp \ll 8\mu \ll dx \ll r^2$, (B) $\hat{a}^{\wedge} R^2 \ll dp \ll 4\mu \ll dx \ll r^2$, (C) $\hat{a}^{\wedge} R^2 \ll dp \ll 2\mu \ll dx \ll r^2$, (D) $\hat{a}^{\wedge} R^2 \ll dp \ll \mu \ll dx \ll r^2$, 6 © <https://assignbuster.com/me-gate-paper-2009/>

All rights reserved by GATE Forum Educational Services Pvt. Ltd. No part of this booklet may be reproduced or utilized in any form without the P age 6 of 13 written permission. Discuss this questions paper at www.gateforum.com.

MEİİĞ GATE Paper 2009 www.gateforum.com 35. A solid shaft of www.JbigDeaL.com Powered the ends. A torque, T_0 is _____ Download from www.JbigDeaL.com diameter, d and length L is fixed at both By © [JbigDeaL.com](http://www.JbigDeaL.com) _____

applied at a distance, $L/4$ from the left end as shown in the figure given

below T_0 $L/4$ $3L/4$ The maximum shear stress in the shaft is (A) $36.16T_0$

İİĞ (B) $12T_0$ (C) İİĞ $8T_0$ İİĞ (D) $4T_0$ İİĞ An epicyclic gear train is

shown schematically in the adjacent figure The sun gear 2 on the input shaft is a 20 teeth external gear. The planet gear 3 is a 40 teeth external gear.

The ring gear 5 is a 100 teeth internal gear. The ring gear 5 is fixed and the gear 2 is rotating at 50 rpm ccw (ccw= counter-clockwise and cw=

clockwise) The arm 4 attached to the output shaft will rotate at $-4/3 \cdot 5/2$ (A)

10 rpm ccw 37. (B) 10 rpm cw (C) 12 rpm cw (D) 12 rpm ccw A forged steel

link with uniform diameter of 30mm at the centre is subjected to an axial

force that varies from 40kN in compression to 160kN in tension. The tensile

(S_u), yield (S_y) and corrected endurance (S_e) strengths of the steel material

are 600MPa, 420MPa and 240MPa respectively. The factor of safety against

fatigue endurance as per Soderberg's criterion is (A) 1.26 (B) 1.37 (C) 1.45

(D) 2.00 7 © All rights reserved by GATE Forum Educational Services Pvt.

Ltd. No part of this booklet may be reproduced or utilized in any form without the P age 7 of 13 written permission. Discuss this questions paper at www.gateforum.com.

MEİİĞ GATE Paper 2009 www.gateforum.com 38. An

automotive www.JbigDeaL.com weighing 240kg is Powered By © [JbigDeaL.com](http://www.JbigDeaL.com) _____

_____ Download from www.JbigDeaL.com supported on four springs

<https://assignbuster.com/me-gate-paper-2009/>

with linear characteristics. Each of the front two springs have a stiffness of 16MN/m while the stiffness of each rear spring is 32MN/m. The engine speed (in rpm), at which resonance is likely to occur, is (A) 6040 39. (B) 3020 (C) 1424 (D) 955

A vehicle suspension system consists of a spring and a damper. The stiffness of the spring is 3. 6kN/m and the damping constant of the damper is 400Ns/m. If the mass is 50kg, then the damping factor (d) and damped natural frequency (fn), respectively, are (A) 0. 471 and 1. 19Hz (C) 0. 666 and 1. 35Hz 40. (B) 0. 471 and 7. 48Hz (D) 0. 666 and 8. 50Hz

A frame of two arms of equal length L is shown in the adjacent figure. The flexural rigidity of each arm of the frame is EI. The vertical deflection at the point of application of load P is (A) $PL^3/3EI$ (B) $2PL^3/3EI$ L P 3 (C) (D) $4PL^3/3EI$ L

A uniform rigid rod of mass M and length L is hinged at one end as shown in the adjacent figure. A force P is applied at a distance of $2L/3$ from the hinge so that the rod swings to the right. The reaction at the hinge is (A) -P (B) 0 $2L/3$ L (C) $P/3$ P (D) $2P/3$ 8

© All rights reserved by GATE Forum Educational Services Pvt. Ltd. No part of this booklet may be reproduced or utilized in any form without the P age 8 of 13 written permission. Discuss this questions paper at www.gateforum.com. MEI gate Paper 2009 www.gateforum.com

42. Match the approaches given below to

_____ Download from www.jbigdeal.com perform stated kinematics / dynamics Powered By © jbigdeal_____ analysis of machine. Analysis Approach P. Continuous relative rotation 1. D' Alembert's principle Q. Velocity and acceleration 2. Grubler's criterion R. Mobility 3. Grashoff's law S. Dynamic-static analysis 4. Kennedy's theorem (A) P-1, Q-2, R-3, S-4 (C) P-2, Q-3, R-4, S-1 43. (B) P-3, Q-4, R-2, S-1 (D) P-4, Q-2, R-1, S-3

A company uses 2555 units of an item annually. Delivery lead time is 8 days. The recorder

<https://assignbuster.com/me-gate-paper-2009/>

point (in number of units) to achieve optimum inventory is (A) 74.4 (B) 85.6 (C) 56 (D) 60 Consider the following Linear Programming Problem (LPP):

Maximize $z = 3x_1 + 2x_2$ Subject to $x_1 \leq 4$, $x_2 \leq 6$, $3x_1 + 2x_2 \leq 18$

$x_1 \geq 0$, $x_2 \geq 0$ (A) The LPP has a unique optimal solution (B) The LPP is infeasible (C) The LPP is unbounded (D) The LPP has multiple optimal solutions

45. Six jobs arrived in a sequence as given below: Jobs Processing Time (days) I 4 II 9 III 5 IV 10 V 6 VI 8 Average flow time (in days) for the above jobs using Shortest Processing Time rule is (A) 20.83 (B) 23.16 (C) 125.00 (D) 139.00

© All rights reserved by GATE Forum Educational Services Pvt. Ltd. No part of this booklet may be reproduced or utilized in any form without the written permission. Discuss this questions paper at www.gateforum.com. ME Gate Paper 2009 www.gateforum.com

46. Minimum shear angle _____ Download from www.JbigDeal.com with a cutting tool of zero rake angle _____ Powered By © [JbigDeal.com](http://www.JbigDeal.com) _____ is (A) 0.047 (B) 0.5 (C) 1.0 (D) 2.0

Electrochemical machining is performed to remove material from an iron surface of 20mm × 20mm under the following conditions: = 0.2mm Inter electrode gap Supply voltage (DC) = 12V Specific resistance of electrolyte = 2 Ω/cm = 55.85

Atomic weight of Iron = 56 Valency of Iron = 2 Faraday's constant = 96540 Coulombs Faraday's constant The material removal rate (in g/s) is (A) 0.347148 (B) 3.471 (C) 34.71 (D) 347.1

Match the following NC Code Definition P. M05 1. Absolute coordinate system Q. G01 2. Dwell R. G04 3. Spindle stop S. G90 4. Linear interpolation (A) P-2, Q-3, R-4, S-1 (C) P-3, Q-4, R-2, S-1 49. (B) P-3, Q-4, R-1, S-2 (D) P-4, Q-3, R-2, S-1

What are the upper and lower limits of the shaft represented by 60 f8? Use the following data: Diameter 60 lies in the diameter step of 50-80mm Fundamental tolerance unit, i , in $\mu\text{m} = 0.$

$45D_{1/3+0.001D}$, where D is the representative size in mm; Tolerance value for IT8 = 25 μ m. Fundamental deviation for 'f' shaft = -5.5D^{0.41} (A) Lower limit = 59.924mm, Upper Limit = 59.970mm (B) Lower limit = 59.954mm, Upper Limit = 60.000mm (C) Lower limit = 59.970mm, Upper Limit = 60.016mm (D) Lower limit = 60.000mm, Upper Limit = 60.046mm

© All rights reserved by GATE Forum Educational Services Pvt. Ltd. No part of this booklet may be reproduced or utilized in any form without the written permission. Discuss this questions paper at www.gateforum.com.

Match the items w Column I and Column _____ Download from in www.JbigDeal.com II. Powered By © JbigDeal _____ Column I Column II

P. Metallic Chills 1. Support for the core Q. Metallic Chaplets 2. Reservoir of the molten metal R. Riser 3. Control cooling of critical sections S. Exothermic Padding 4. Progressive solidification (A) P-1, Q-3, R-2, S-4 (B) P-1, Q-4, R-2, S-3 (C) P-3, Q-4, R-2, S-1 (D) P-4, Q-1, R-2, S-3

Common Data Questions: 51 & 52 The inlet and the outlet conditions of stream for an adiabatic steam turbine are as indicated in the notations are as usually followed $h_1 = 3200\text{kJ/kg}$ $V_1 = 160\text{m/s}$ figure. $Z_1 = 10\text{m}$ $P_1 = 3\text{MPa}$ $h_2 = 2600\text{kJ/kg}$ $V_2 = 100\text{m/s}$ $Z_2 = 6\text{m}$ $P_2 = 70\text{kPa}$

51. If mass flow rate of steam through the turbine is 20kg/s, the power output of the turbine (in MW) is (A) 12.157 (B) 12.941 (C) 168.001 (D) 168.785

Assume the above turbine to be part of a simple Rankine cycle. The density of water at the inlet to the pump is 1000kg/m³. Ignoring kinetic and potential energy effects, the specific work (in kJ/kg) supplied to the pump is (A) 0.293 (B) 0.351 (C) 2.930 (D) 3.510

Common Data Questions: 53 & 54 Radiative heat transfer is intended between the inner surfaces of two very large isothermal parallel metal plates. While the upper plate (designated as

<https://assignbuster.com/me-gate-paper-2009/>

plate 1) is a black surface and is the warmer one being maintained at 727°C , the lower plate (plate 2) is a diffuse and gray surface with an emissivity of 0.7 and is kept at 227°C . Assume that the surfaces are sufficiently large to form a two-surface enclosure and steady state conditions to exist. Stefan Boltzmann constant is given as $5.67 \times 10^{-8} \text{W/m}^2\text{K}^4$

© All rights reserved by GATE Forum Educational Services Pvt. Ltd. No part of this booklet may be reproduced or utilized in any form without the written permission. Discuss this questions paper at www.gateforum.com.

MEİİĞ GATE Paper 2009 www.gateforum.com 53. The irradiation (in W/m^2) for the upper plate is _____ Download from www.JbigDeal.com

(A) 2.5 (B) 3.6 (C) 17.0 (D) 19.5

If plate 1 is also a diffuse and gray surface with an emissivity value of 0.8, the net radiation heat exchange (in kW/m^2) between plate 1 and plate 2 is (A) 17.0 (B) 19.0 (C) 23.0 (D) 31.7

Common Data Questions: 55 & 56 Consider the following PERT network: 3 1 2 6 5 7 4

Activity	Most likely time (days)	Pessimistic time (days)
1-2	1	2
1-3	5	6
1-4	3	5
2-5	5	7
3-5	2	4
4-6	5	6
5-6	4	5
6-7	4	6
7-4	6	8

55. Optimistic time (days) 2 3 4 The critical path duration of the network (in days) is (A) 11 (B) 14 (C) 17 (D) 18

(C) 0.77 (D) 1.66

The standard deviation of the critical path is (A) 0.33 (B) 0.55

© All rights reserved by GATE Forum Educational Services Pvt. Ltd. No part of this booklet may be reproduced or utilized in any form without the written permission. Discuss this questions paper at www.gateforum.com.

MEİİĞ GATE Paper 2009 www.gateforum.com Linked Answer Questions: Q. 57 to _____ Download from www.JbigDeal.com

Q. 60 Carry Two Marks Each Powered By © <https://assignbuster.com/me-gate-paper-2009/>

Statement for Linked Answer Questions: 57 & 58 In a machining experiment, tool life was found to vary with the cutting speed in the following manner: Cutting speed (m/min) 60 81 90 57. Tool life (minutes) 36 The exponent (n) and constant (k) of the Taylor's tool life equation are (A) $n = 0.5$ and $k = 540$ (C) $n = 1$ and $k = 4860$ (B) $n = 1$ and $k = 4860$ (D) $n = 0.5$ and $k = 1.155$ What is the percentage increase in tool life when the cutting speed is halved? (A) 50% (B) 200% (C) 300% (D) 400%

Statement for Linked Answer Questions: 59 & 60 A 20° full depth involute spur pinion of 4mm module and 21 teeth is to transmit 15kW at 960rpm. Its face width is 25mm. 59. The tangential force transmitted (in N) is (A) 3552 60. (B) 2611 (C) 1776 (D) 1305 Given that the tooth geometry factor is 0.32 and the combined effect of dynamic load and allied factors intensifying the stress is 1.5; the minimum allowable stress (in MPa) for the gear material is (A) 242.0 (B) 166.5 (C) 121.0 (D) 74.0

© All rights reserved by GATE Forum Educational Services Pvt. Ltd. No part of this booklet may be reproduced or utilized in any form without the P age 13 of 13 written permission. Discuss this questions paper at www.gateforum.com.