

Connectionism coming of age: legacy and future challenges

[Health & Medicine](#)



About 50 Years after the Introduction of the Perceptron and Some 25 Years after the Introduction of PDP Models, Where are we Now?

In 1986, Rumelhart and McClelland took the cognitive science community by storm with the Parallel Distributed Processing (PDP) framework. Rather than abstracting from the biological substrate as was sought by the “information processing” paradigms of the 1970s, connectionism, as it has come to be called, embraced it. An immediate appeal of the connectionist agenda was its aim: to construct at the algorithmic level models of cognition that were compatible with their implementation in the biological substrate.

The PDP group argued that this could be achieved by turning to networks of artificial neurons, originally introduced by [McCulloch and Pitts \(1943\)](#) which the group showed were able to provide insights into a wide range of psychological domains, from categorization, to perception, to memory, to language. This work built on an earlier formulation by [Rosenblatt \(1958\)](#) who introduced a simple type of feed-forward neural network called the perceptron. Perceptrons were limited to solving simple linearly-separable problems and although networks composed of perceptrons were known to be able to compute any Boolean function (including XOR, [Minsky and Papert, 1969](#)), there was no effective way of training such networks. In 1986, Rumelhart, Hinton and Williams introduced the back-propagation algorithm, providing an effective way of training multi-layered neural networks, which could easily learn non linearly-separable functions. In addition to providing the field with an effective learning algorithm, the PDP group published a series of demonstrations of how long standing questions in cognitive

psychology could be elegantly solved using simple learning rules, distributed representations, and interactive processing.

To take a classic example, consider the word-superiority effect, in which people can detect letters within a word faster than individual letters or letters within a non-word ([Reicher, 1969](#)). This result is difficult to square with serial “ information-processing” theories of cognition that were dominant at the time (how could someone recognize “ R” before “ FRIEND” if recognizing the word required recognizing the letters?). Accounting for such findings demanded a framework which could naturally accommodate interactive processes within a bidirectional flow of information. The so-called “ Interactive-activation model” ([McClelland and Rumelhart, 1981](#)) provided just such a framework.

The connectionist paradigm was not without its critics. The principal critiques can be divided into three classes. First, some neuroscientists ([Crick, 1989](#)) questioned the biological plausibility of backpropagation, when they failed to observe experimentally complex and differentiated back-propagating signals that are required to learn in multi-layered neural networks. A second critique concerned stability-plasticity of the learned representations in these models. Some phenomena require the ability to rapidly learn new information, but sometimes newly learned knowledge overwrites previously learned information (catastrophic interference; [McCloskey and Cohen, 1989](#)). Third, representing spatial and temporal invariance—something that apparently came easily to people—was difficult for models, e. g., recognizing that the letter “ T” in “ TOM” was the “ same” as the “ T” in “ POT.” This invariance

problem was typically solved by multiplying a large number of hard-wired units that were space- or time-locked (see e. g., [McClelland and Elman, 1986](#)). Finally, critics pointed out that the networks were incapable of learning true rules on which a number of human behavioral, namely language-learning was thought to depend (e. g., [Marcus, 2003](#); cf. [Fodor and Pylyshyn, 1988](#); [Seidenberg, 1999](#)).

The connectionist approach has embraced these challenges: Although some connectionist models continue to rely on backpropagation, others have moved to more biologically realistic learning rules ([Giese and Poggio, 2003](#); [Masquelier and Thorpe, 2007](#)). Far from being a critical flaw of connectionism, the phenomenon of catastrophic interference ([Mermilliod et al., 2013](#)) proved to be a feature that led to the development of complementary learning systems ([McClelland et al., 1995](#)).

Progress has also been made on the invariance problem. For example, within the speech domain representing the similarity between similar speech sounds regardless of their location within a word has been addressed in the past by [Grossberg and Myers \(2000\)](#) and [Norris \(1994\)](#) and this issue presents a new more streamlined and computationally efficient model ([Hannagan et al., 2013](#)). An especially powerful approach to solving the location invariance problem in the visual domain is presented by [Di Bono and Zorzi \(2013\)](#), also in this issue.

A key challenge for connectionism is to explain the learning of abstract structural representations. The use of recurrent networks ([Elman, 1990](#); [Dominey, 2013](#)) and self-organizing maps, has captured important aspects

of language learning (e. g., [Mayor and Plunkett, 2010](#); [Li and Zhao, 2013](#)), while work on deep learning ([Hinton and Salakhutdinov, 2006](#)) has made it possible to model the emergence of structured and abstract representations within multi-layered hierarchical networks ([Zorzi et al., 2013](#)). The work on verbal analogies by [Kollias and McClelland \(2013\)](#) continues to address the challenges of modeling more abstract representations, but truly understanding how neural architectures give rise to symbolic cognition is a gap that remains. Although learning and representing formal language rules may not be completely outside of the abilities of neural networks (e. g., [Chang, 2009](#)), it seems clear that understanding human cognition requires understanding how we solve these symbolic problems ([Clark and Karmiloff-Smith, 1993](#); [Lupyan, 2013](#)). Future generations of connectionist modelers may wish to fill this gap and in so doing provide a fuller picture of how neural networks give rise to intelligence of the sort enables us to ponder the very workings of our cognition.

What's Next?

The articles assembled in this issue demonstrate the range of topics currently addressed by connectionist models: from word learning in atypical populations ([Sims et al., 2013](#)), to sentence processing ([Hsiao and MacDonald, 2013](#)), to multimodal processing ([Bergmann et al., 2013](#)), to interactions between language and vision ([Smith et al., 2013](#)). We expect this diversity to continue to increase. We also hope to see greater increasing integration between connectionism and a computationally similar but philosophically distinct models employing Bayesian inference. Although the computational similarities between these two approaches have been

previously recognized ([McClelland, 1998](#)), detailed tutorials like the one contained in this volume ([McClelland, 2013](#)) provide new clarity on the relationship between these two approaches.

The influence of theoretical constructs introduced by the connectionist approach have become part and parcel of cognitive science (although they are now often not accompanied by the label “connectionism” or “PDP”). The distributed representations that challenge classical symbolic models and which emerge naturally in neural networks are now no longer theoretical constructs and can be directly observed in the brain ([Kriegeskorte et al., 2008](#) ; [Chang et al., 2010](#)). Evidence for rapid warping of these representations by task demands (of the sort described by e. g., [McClelland and Rogers, 2003](#)) is also being confirmed through modern neuroimaging (e. g., [Çukur et al., 2013](#)) ¹. Many connectionist models have stressed prediction as a way of learning structure and statistical inputs (e. g., [Dell and Chang, 2014](#)). This too finds wide support in contemporary neuroscience ([Friston, 2010](#)) leading some to even argue that prediction is the unifying feature of all cognitive and perceptual processes ([Clark, 2013](#) , for review). Interactive processing—another core feature of the connectionist paradigm—has become similarly foundational. The interplay between bottom-up and top-down information is now recognized to be critical from everything as simple as simply detecting the presence of a visual stimulus, to consciousness itself (e. g., [Dehaene et al., 2003](#) ; [Gilbert and Sigman, 2007](#) ; [Lupyan and Ward, 2013](#)).

Finally, contemporary neural networks, most notably those utilizing so called deep-learning, have found success in solving practical problems such as image and speech recognition, and natural language processing. For example, algorithms based on the deep-learning approach are now used by Google to extract high-level features from images with, in some cases, above-human performance ([Ciresan et al., 2011](#); [Le et al., 2011](#)).

Acknowledgments

This work is supported by the Swiss National Science Foundation Grant 131700 awarded to Julien Mayor. Franklin Chang is supported by Leverhulme Trust Research Project Grant (RPG-158).

Footnotes

1. [^]It is useful to note that the methods that make these analyses possible, most notably multi-voxel pattern analyses (MVPA, e. g., [Norman et al., 2006](#)) and “representational dissimilarity matrices” ([Kriegeskorte et al., 2008](#)) are adaptations of methods developed for analyzing dynamics of artificial neural networks.

References

Bergmann, C., ten Bosch, L., Fikkert, P., and Boves, L. (2013). A computational model to investigate assumptions in the headturn preference procedure. *Front. Psychol.* 4: 676. doi: 10.3389/fpsyg.2013.00676

[Pubmed Abstract](#) | [Pubmed Full Text](#) | [CrossRef Full Text](#)

Chang, E. F., Rieger, J. W., Johnson, K., Berger, M. S., Barbaro, N. M., and Knight, R. T. (2010). Categorical speech representation in human superior temporal gyrus. *Nat. Neurosci.* 13, 1428–1432. doi: 10.1038/nn.2641

[Pubmed Abstract](#) | [Pubmed Full Text](#) | [CrossRef Full Text](#)

Chang, F. (2009). Learning to order words: a connectionist model of heavy NP shift and accessibility effects in Japanese and English. *J. Mem. Lang.* 61, 374–397. doi: 10.1016/j.jml.2009.07.006

[CrossRef Full Text](#)

Ciresan, D. C., Meier, U., Masci, J., Gambardella, L. M., and Schmidhuber, J. (2011). “Flexible, high performance convolutional neural networks for image classification,” in *International Joint Conference on Artificial Intelligence IJCAI-2011*. (Barcelona), 1237–1242.

Clark, A. (2013). Whatever next? Predictive brains, situated agents, and the future of cognitive science. *Behav. Brain Sci.* 36, 181–204. doi: 10.1017/S0140525X12000477

[Pubmed Abstract](#) | [Pubmed Full Text](#) | [CrossRef Full Text](#)

Clark, A., and Karmiloff-Smith, A. (1993). The cognizer's innards: a psychological and philosophical perspective on the development of thought. *Mind Lang.* 8, 487–519. doi: 10.1111/j.1468-0017.1993.tb00299.x

[Pubmed Abstract](#) | [Pubmed Full Text](#) | [CrossRef Full Text](#)

Crick, F. (1989). The recent excitement about neural networks. *Nature* 337, 129–132. doi: 10.1038/337129a0

[Pubmed Abstract](#) | [Pubmed Full Text](#) | [CrossRef Full Text](#)

Çukur, T., Nishimoto, S., Huth, A. G., and Gallant, J. L. (2013). Attention during natural vision warps semantic representation across the human brain. *Nat. Neurosci.* 16, 763–770. doi: 10.1038/nn.3381

[Pubmed Abstract](#) | [Pubmed Full Text](#) | [CrossRef Full Text](#)

Dehaene, S., Sergent, C., and Changeux, J.-P. (2003). A neuronal network model linking subjective reports and objective physiological data during conscious perception. *Proc. Natl. Acad. Sci. U. S. A.* 100, 8520–8525. doi: 10.1073/pnas.1332574100

[Pubmed Abstract](#) | [Pubmed Full Text](#) | [CrossRef Full Text](#)

Dell, G. S., and Chang, F. (2014). The P-Chain: Relating sentence production and its disorders to comprehension and acquisition. *Philos. Trans. R. Soc. B Biol. Sci.* 369, 20120394. doi: 10.1098/rstb.2012.0394

[Pubmed Abstract](#) | [Pubmed Full Text](#) | [CrossRef Full Text](#)

Di Bono, M. G., and Zorzi, M. (2013). Deep generative learning of location-invariant visual word recognition. *Front. Psychol.* 4: 635. doi: 10.3389/fpsyg.2013.00635

[Pubmed Abstract](#) | [Pubmed Full Text](#) | [CrossRef Full Text](#)

Dominey, P. F. (2013). Recurrent temporal networks and language acquisition—from corticostriatal neurophysiology to reservoir computing. *Front. Psychol.* 4: 500. doi: 10.3389/fpsyg.2013.00500

[Pubmed Abstract](#) | [Pubmed Full Text](#) | [CrossRef Full Text](#)

Elman, J. (1990). Finding structure in time. *Cogn. Sci.* 14, 179–212. doi: 10.1207/s15516709cog1402_1

[CrossRef Full Text](#)

Fodor, J. A., and Pylyshyn, Z. W. (1988). Connectionism and cognitive architecture: a critical analysis. *Cognition* 28, 3–71. doi: 10.1016/0010-0277(88)90031-5

[Pubmed Abstract](#) | [Pubmed Full Text](#) | [CrossRef Full Text](#)

Friston, K. (2010). The free-energy principle: a unified brain theory? *Nat. Rev. Neurosci.* 11, 127–138. doi: 10.1038/nrn2787

[Pubmed Abstract](#) | [Pubmed Full Text](#) | [CrossRef Full Text](#)

Giese, M., and Poggio, T. (2003). Neural mechanisms for the recognition of biological movements and action. *Nat. Rev. Neurosci.* 4, 179–192. doi: 10.1038/nrn1057

[Pubmed Abstract](#) | [Pubmed Full Text](#) | [CrossRef Full Text](#)

Gilbert, C. D., and Sigman, M. (2007). Brain states: top-down influences in sensory processing. *Neuron* 54, 677–696. doi: 10.1016/j.neuron.2007.05.019

[Pubmed Abstract](#) | [Pubmed Full Text](#) | [CrossRef Full Text](#)

Grossberg, S., and Myers, C. W. (2000). The resonant dynamics of speech perception: interword integration and duration-dependent backward effects. *Psychol. Rev.* 107, 735. doi: 10.1037/0033-295X.107.4.735

[Pubmed Abstract](#) | [Pubmed Full Text](#) | [CrossRef Full Text](#)

Hannagan, T., Magnuson, J. S., and Grainger, J. (2013). Spoken word recognition without a TRACE. *Front. Psychol.* 4: 563. doi: 10.3389/fpsyg.2013.00563

[Pubmed Abstract](#) | [Pubmed Full Text](#) | [CrossRef Full Text](#)

Hinton, G. E., and Salakhutdinov, R. R. (2006). Reducing the dimensionality of data with neural networks. *Science* 313, 504–507. doi: 10.1126/science.1127647

[Pubmed Abstract](#) | [Pubmed Full Text](#) | [CrossRef Full Text](#)

Hsiao, Y., and MacDonald, M. C. (2013). Experience and generalization in a connectionist model of Mandarin Chinese relative clause processing. *Front. Psychol.* 4: 767. doi: 10.3389/fpsyg.2013.00767

[Pubmed Abstract](#) | [Pubmed Full Text](#) | [CrossRef Full Text](#)

Kollias, P., and McClelland, J. L. (2013). Context, cortex, and associations: a connectionist developmental approach to verbal analogies. *Front. Psychol.* 4: 857. doi: 10.3389/fpsyg. 2013. 00857

[Pubmed Abstract](#) | [Pubmed Full Text](#) | [CrossRef Full Text](#)

Kriegeskorte, N., Mur, M., Ruff, D. A., Kiani, R., Bodurka, J., Esteky, H., et al. (2008). Matching categorical object representations in inferior temporal cortex of man and monkey. *Neuron* 60, 1126–1141. doi: 10.1016/j.neuron. 2008. 10. 043

[Pubmed Abstract](#) | [Pubmed Full Text](#) | [CrossRef Full Text](#)

Le, Q. V., Ranzato, M.'A., Monga, R., Devin, M., Chen, K., Corrado, G. S., et al. (2011). Building high-level features using large scale unsupervised learning. *arXiv preprint arXiv: 1112. 6209.*

Li, P., and Zhao, X. (2013). Self-organizing map models of language acquisition. *Front. Psychol.* 4: 828. doi: 10.3389/fpsyg. 2013. 00828

[Pubmed Abstract](#) | [Pubmed Full Text](#) | [CrossRef Full Text](#)

Lupyan, G. (2013). The difficulties of executing simple algorithms: why brains make mistakes computers don't. *Cognition* 129, 615–636. doi: 10.1016/j. cognition. 2013. 08. 015

[Pubmed Abstract](#) | [Pubmed Full Text](#) | [CrossRef Full Text](#)

Lupyan, G., and Ward, E. J. (2013). Language can boost otherwise unseen objects into visual awareness. *Proc. Natl. Acad. Sci. U. S. A.* 110, 14196–14201. doi: 10.1073/pnas.1303312110

[Pubmed Abstract](#) | [Pubmed Full Text](#) | [CrossRef Full Text](#)

Marcus, G. F. (2003). *The Algebraic Mind: Integrating Connectionism and Cognitive Science*. Cambridge: The MIT Press.

Masquelier, T., and Thorpe, S. J. (2007). Unsupervised learning of visual features through spike timing dependent plasticity. *PLoS Comput. Biol.* 3: e31. doi: 10.1371/journal.pcbi.0030031

[Pubmed Abstract](#) | [Pubmed Full Text](#) | [CrossRef Full Text](#)

Mayor, J., and Plunkett, K. (2010). A neurocomputational model of taxonomic responding and fast mapping in early word learning. *Psychol. Rev.* 117, 1–31. doi: 10.1037/a0018130

[Pubmed Abstract](#) | [Pubmed Full Text](#) | [CrossRef Full Text](#)

McClelland, J. L. (1998). “Connectionist models and Bayesian inference,” in *Rational Models of Cognition*, eds M. Oaksford and N. Chater (Oxford: Oxford University Press), 21–53.

McClelland, J. L. (2013). Integrating probabilistic models of perception and interactive neural networks: a historical and tutorial review. *Front. Psychol.* 4: 503. doi: 10.3389/fpsyg.2013.00503

[Pubmed Abstract](#) | [Pubmed Full Text](#) | [CrossRef Full Text](#)

<https://assignbuster.com/connectionism-coming-of-age-legacy-and-future-challenges/>

McClelland, J. L., and Elman, J. L. (1986). The TRACE model of speech perception. *Cogn. Psychol.* . 18, 1–86. doi: 10. 1016/0010-0285(86)90015-0

[Pubmed Abstract](#) | [Pubmed Full Text](#) | [CrossRef Full Text](#)

McClelland, J. L., McNaughton, B. L., and O'Reilly, R. C. (1995). Why there are complementary learning-systems in the hippocampus and neocortex - insights from the successes and failures of connectionist models of learning and memory. *Psychol. Rev.* . 102, 419–457.

[Pubmed Abstract](#) | [Pubmed Full Text](#)

McClelland, J. L., and Rogers, T. T. (2003). The parallel distributed processing approach to semantic cognition. *Nat. Rev. Neurosci.* . 4, 310–322. doi: 10. 1038/nrn1076

[Pubmed Abstract](#) | [Pubmed Full Text](#) | [CrossRef Full Text](#)

McClelland, J. L., and Rumelhart, D. E. (1981). An interactive activation model of context effects in letter perception: I. An account of basic findings. *Psychol. Rev.* . 88, 375–407. doi: 10. 1037/0033-295X. 88. 5. 375

[CrossRef Full Text](#)

McCloskey, M., and Cohen, N. J. (1989). Catastrophic interference in connectionist networks: the sequential learning problem. *Psychol. Learn. Motiv.* . 24, 109–164. doi: 10. 1016/S0079-7421(08)60536-8

[CrossRef Full Text](#)

McCulloch, W. S., and Pitts, W. (1943). A logical calculus of the ideas immanent in nervous activity. *Bull. Math. Biophys.* . 5, 115–133. doi: 10.1007/BF02478259

[Pubmed Abstract](#) | [Pubmed Full Text](#) | [CrossRef Full Text](#)

Mermilliod, M., Bugaiska, A., and Bonin, P. (2013). The stability-plasticity dilemma: investigating the continuum from catastrophic forgetting to age-limited learning effects. *Front. Psychol.* . 4: 504. doi: 10.3389/fpsyg.2013.00504

[Pubmed Abstract](#) | [Pubmed Full Text](#) | [CrossRef Full Text](#)

Minsky, M. L., and Papert, S. A. (1969). *Perceptrons* . Cambridge, MA: MIT Press.

Norman, K. A., Polyn, S. M., Detre, G. J., and Haxby, J. V. (2006). Beyond mind-reading: multi-voxel pattern analysis of fMRI data. *Trends Cogn. Sci.* . 10, 424–430. doi: 10.1016/j.tics.2006.07.005

[Pubmed Abstract](#) | [Pubmed Full Text](#) | [CrossRef Full Text](#)

Norris, D. (1994). Shortlist: a connectionist model of continuous speech recognition. *Cognition* 52, 189–234. doi: 10.1016/0010-0277(94)90043-4

[Pubmed Abstract](#) | [Pubmed Full Text](#) | [CrossRef Full Text](#)

Reicher, G. M. (1969). Perceptual recognition as a function of meaningfulness of stimulus material. *J. Exp. Psychol.* . 81, 275. doi: 10.1037/h0027768

[Pubmed Abstract](#) | [Pubmed Full Text](#) | [CrossRef Full Text](#)

Rosenblatt, F. (1958). The perceptron: a probabilistic model for information storage and organization in the brain. *Psychol. Rev.* 65, 386. doi: 10.1037/h0042519

[Pubmed Abstract](#) | [Pubmed Full Text](#) | [CrossRef Full Text](#)

Rumelhart, D. E., Hinton, G. E., and Williams, R. J. (1986). Learning representations by back-propagating errors *Nature* 323, 9. doi: 10.1038/323533a0

[CrossRef Full Text](#)

Rumelhart, D. E., and McClelland, J. L. (1986). *Parallel Distributed Processing: Explorations in the Microstructure of Cognition*. Vol. 1. Cambridge, MA: Foundations MIT Press.

Seidenberg, M. S. (1999). Do infants learn grammar with algebra or statistics? *Science* 284, 434–435. author reply: 436–437.

[Pubmed Abstract](#) | [Pubmed Full Text](#)

Sims, C. E., Schilling, S. M., and Colunga, E. (2013). Beyond modeling abstractions: learning nouns over developmental time in atypical populations and individuals. *Front. Psychol.* 4: 871. doi: 10.3389/fpsyg.2013.00871

[Pubmed Abstract](#) | [Pubmed Full Text](#) | [CrossRef Full Text](#)

Smith, A. C., Monaghan, P., and Huettig, F. (2013). An amodal shared resource model of language-mediated visual attention. *Front. Psychol.* 4: 528. doi: 10.3389/fpsyg. 2013. 00528

[Pubmed Abstract](#) | [Pubmed Full Text](#) | [CrossRef Full Text](#)

Zorzi, M., Testolin, A., and Stoianov, I. P. (2013). Modeling language and cognition with deep unsupervised learning: a tutorial overview. *Front. Psychol.* 4: 515. doi: 10.3389/fpsyg. 2013. 00515

[Pubmed Abstract](#) | [Pubmed Full Text](#) | [CrossRef Full Text](#)